



FWD04A



FWD04A



ECFWR6



- > System montowania na ścianie lub na suficie
- > Podłączenie kanałów bezpośrednio do jednostki
- > Fitr powietrza w standardzie: wyjmowany od dołu

FWD			2-PIPE							4-PIPE							
			04	06	08	10	012	016	018	04	06	08	10	012	016	018	
Pobór mocy	W		234	349	443		714	1197		234	349	443		714	1197		
Wydajność	Chłodzenie capacity	Total capacity	kW	3.90	6.20	7.80	8.82	11.90	16.40	18.30	3.90	6.20	7.80	8.82	11.90	16.40	18.30
	Wydajność grzewcza (2-rurowe)		kW	4.05	7.71	9.43	10.79	14.45	19.81	21.92							
	Wydajność grzewcza (4-rurowe)		kW	-						4.49	6.62	9.21		15.86	21.15		
Wymiary	Wys.xSzer.xGł.		mm	280x754x559	280x964x559	280x1,174x559		352x1,174x718	352x1,384x718		280x754x559	280x964x559	280x1,174x559		352x1,174x718	352x1,384x718	
Ciężar jednostki			kg	33	41	47	49	65	77	80	35	43	50	52	71	83	86
Sound level	Poziom mocy akustycznej		dBA	66	69	72		74	78		66	69	72		74	78	
Water pressure drop	Chłodzenie		kPa	17	24		16	26	34	45	17	24		16	26	34	45
	Grzanie		kPa	14	20		13	21	28	37	9	15	13		12	16	
Wentylator	Przepływ powietrza		m³/h	800	1,250	1,600		2,200	3,000		800	1,250	1,600		2,200	3,000	
	Ciśnienie dyspozycyjne		Pa	66	58	68	64	97	145	134	63	53	63	59	92	138	128
Przyłącze wodne	Standardowy wymiennik ciepła		cale	3/4				1			3/4			1			
Zasilanie elektryczne			V / f / Hz	230/1/50													